

UNCLASSIFIED

Defense Technical Information Center
Compilation Part Notice

ADP022472

TITLE: Sheet-beam Electron Gun Design for Millimeter and
Sub-millimeter Wave Vacuum Electronic Sources

DISTRIBUTION: Approved for public release, distribution unlimited

This paper is part of the following report:

TITLE: 2006 IEEE International Vacuum Electronics Conference held
jointly with 2006 IEEE International Vacuum Electron Sources Held in
Monterey, California on April 25-27, 2006

To order the complete compilation report, use: ADA453924

The component part is provided here to allow users access to individually authored sections
of proceedings, annals, symposia, etc. However, the component should be considered within
the context of the overall compilation report and not as a stand-alone technical report.

The following component part numbers comprise the compilation report:
ADP022420 thru ADP022696

UNCLASSIFIED

Sheet-beam Electron Gun Design for Millimeter and Sub-millimeter Wave Vacuum Electronic Sources

B.G. Danly

Electronics Science & Technology
Division, Code 6841
U.S. Naval Research Laboratory
4555 Overlook Ave., SW
Washington, DC 20375
danly@nrl.navy.mil

J.J. Petillo

Science Applications International
Corporation
Suite 130
20 Burlington Mall Rd
Burlington, MA 01803

J.X. Qiu & B. Levush

Vacuum Electronics Branch
Code 6840
U.S. Naval Research Laboratory
4555 Overlook Ave., SW
Washington, DC 20375

Abstract: *We investigate the application of sheet beams to slowwave sources as a means to increase output power. Our interest is for compact vacuum electronic devices in the millimeter and submillimeter regimes. We consider previous work done on orotrons, clinitrons & backward wave oscillators, and investigate methods to enhance operation into the submillimeter region of the spectrum. We use MICHELLE to model ~40 micron thin sheet beams for such devices.*

Keywords: Sheet beams; sheet beam sources; sheet beam guns; orotron, clinitron; backward wave oscillators, sources, sheet beam formation; beam optics; MICHELLE; Voyager.

Introduction

Compact millimeter and submillimeter wave vacuum electronic sources have a variety of limitations which prevent them from achieving higher output powers. In some cases the limitation in output power can be alleviated through the use of spatially distributed or sheet electron beams. In slowwave sources such as klystrons and traveling wave tubes (TWTs) the use of sheet beams and appropriate circuits can, at least in principle, be utilized to increase power of the device. Several efforts are now underway with that objective in mind (see, for example, [1]). For vacuum electronic sources operating in the upper millimeter wave bands, such as the orotrons [2,3] (or Smith-Purcell free-electron laser), clinitrons [4], and backward wave oscillators (BWOs) similar performance increases can be expected, and in fact such approaches certainly play a role in the present day achievement of power for these devices. Nevertheless, operation of these devices into the submillimeter portion of the spectrum has been limited by a number of technical challenges, including the electron beam generation and limitations on beam current density, as well as manufacturing issues for the slowwave interaction structure [5, 6].

Background

The design of a sheet beam electron gun is underway at NRL for application to a MM/SMM wave orotron. The gun

design parameters are for a beam of 3 mm by 40 μm (aspect ratio of 75:1), and a total current of 50 - 100 mA. The smaller of these dimensions is set by the requirement that the beam thickness be smaller than the transverse scale length of $L_{\perp} = \gamma\beta\lambda/2\pi$. In principle such a beam thickness can be achieved with either focusing gun design of high area convergence or with a gun design of negligible area coverage and operation in an immersed focusing field. The preliminary gun design utilizes an immersed flow design with a flat rectangular cathode. The MICHELLE gun code has been used to model the sheet beam formation and transport; results from a preliminary run are shown in Fig. 1. Further results from this design effort will be presented.

Applications

The maximum design voltage for this electron gun is 15 kV; at this voltage the beam current is 100 mA and the maximum field stress is approximately 82 kV/cm. The cathode current density is approximately 83A/cm², necessitating the use of a LaB₆ or CeB₆ emitter. Such emitters are available commercially [7]. The focusing field for the gun is assumed to be 8 kG, and will be provided by a Magic sphere permanent magnet, previously manufactured under an ARL contract with CPI-CMP.

References

1. B.E. Carlsten. Modal analysis and gain calculations for a sheet electron beam in a ridged waveguide slow-wave structure. *Phys. Plasmas*, 9(12):5088-5096, 2002.
2. F. S. Rusin and G. D. Bogomolov. Orotron - an electronic oscillator with an open resonator and reflecting grating. *Proc. IEEE*, pages 720-722, 1969.
3. K. Mizuno, S. Ono, and Y. Shibata. Two different mode interactions in an electron tube with a Fabry-Perot resonator - the ledatron. *IEEE Trans. Electron Dev.*, 20(8):749-752, 1973.
4. K. Schunemann and D.M. Vavriv. Theory of the clinitron: a grating backward-wave oscillator with

- inclined electron beam. IEEE Trans. Electron Dev., 46(11):2245–2252, 1999.
5. V.L. Bratman, B.S. Dumesht, A.E. Fedotov, Yu.A. Grishin, and F.S. Rusin. Broadband orotron operation at millimeter and submillimeter waves. Int. J. Infrared and Millimeter Waves, 23(11):1595–1601, 2002.
 6. R.L. Ives, M. Caplan, C. Kory, T. Robinson, R. Wilcox, J. Neilson, S. Schwartzkopf, and R. Witherspoon. Design and test of a submillimeter-wave backward wave oscillator. In Sixth International Vacuum Electronics Conference IVEC2005, pages 167–170, 2005.
 7. Applied Physics Technologies, Inc., private communication.




Figure 1: MICHELLE Code run of sheet beam transport in 8 kG immersed field